

Date: \_\_\_\_\_

Job Name \_\_\_\_\_

Purchaser: \_\_\_\_\_

Engineer: \_\_\_\_\_

Submitted To: \_\_\_\_\_

Submitted By: \_\_\_\_\_

Location: \_\_\_\_\_

P.O. No.: \_\_\_\_\_

Architect: \_\_\_\_\_

For:  Reference  Approval  Construction

Tag #: \_\_\_\_\_



**SPECIFICATIONS**

Cooling Capacity BTUH	17,000/17,300
Approx. Sq. Ft. Cooling	700-1000
EER	9.9
Power Supply	208/230V 60Hz
Amps Cooling	7.8/7.3
Electric Heat Cap. BTUH	10,300/12,500
Electric Heat Amps	16.0/14.6
HP Heat Cap. BTUH	14,000/14,300
Heat Pump Amps	7.0/6.5
Heat Pump COP	2.64
Humidity Removal Pts/Hr	4.65
Fan Speeds Cool/Heat/Fan	3/3/3
dB Level (hi/med/low)	72/-70/68
Ventilation Control	Yes
Fan Only	Yes
Air Delivery Max. CFM	541
Maximum Fuse Size	20A
Power Cord	20A Tee NEMA 6-20P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
In-Home Service	Yes
Shipping Weight (lbs.)	159
Dimensions (in.)	Height 18-5/8 Width 26-1/2 Depth 26-1/2

**FEATURES**

- Electronic controls, wireless remote
- Automatic louver swing
- Thru-the-wall or window mount with support bracket included
- Cooling, heating, fan only, energy saver mode. and 24-hour timer
- Switches to supplemental electric heat at 40°F outside temperature



**WARRANTY**

1 Year Parts and Labor, 5 Year Sealed System

**POWER CORD CONFIGURATIONS**

